



CE 0197

- Wide flow rate range from 0.1 ml/h to 1500 ml/h
- Accepts syringe sizes from 10 ml - 100 ml
- Automatic accuracy calibration
- Bolus infusion setting
- Adjustable occlusion pressure
- Adjustable alarm volume

## Specifications

Infusion Rate Range	10 ml syringe	→	0.1-300 ml/h	50/60 ml syringe	→	0.1-1200 ml/h
	20/30 ml syringe	→	0.1-500 ml/h	100 ml syringe	→	0.1-1500 ml/h
Bolus / Purge Rate	10 ml syringe	→	240 ml/h	50/60 ml syringe	→	960 ml/h
	20/30 ml syringe	→	400 ml/h	100 ml syringe	→	1200 ml/h
Bolus Volume	Programmable from 1 to 10 ml					
Flow Rate Increments	0.1-99 ml/h at 0.1 ml/h increments					
	100-1500 ml/h at 1ml/h increments					
Accuracy	± 5% with syringe / ± 2% without syringe					
Occlusion Pressure	0.04 Mpa – 0.12 Mpa / 5.8 PSI – 17.4 PSI					
Alarm Volume	High, Medium, Low					
Safety Protection	Automatic keypad lock					
	Audible & visual alarms					
Alarms	NEAR EMPTY			Syringe disengaged		
	COMPLETE			Mechanical error		
	OCCLUSION			Power source change		
	LOW BATT			Battery depleted		
Power Supply	AC 100-240V 50/60 Hz or DC 12V					
Battery	Built-in rechargeable sealed Ni-MH					
	Pump will operate 3 hours min. at 5 ml/h with fully charged battery					
Safety Approvals	CE 0197, IEC 60601 - 1 - 8: 2003, Type CF, IPX1					
Dimensions	335(L) x 142(W) x 120(H) mm / 13”(L) x 5”(W) x 3”(H)			Net Weight	1.85 Kg / 4 lbs	